



JMAZ®

FIRESTORM F3

Cold Spark Machine w/ RF Remote and Receiver

MAIN FEATURES

- Spark Height Range: 3' – 13' (1-4 meters)
- Warm-Up Time: <8 min
- Spark Height Adjustable: 3 Options (Low, Medium, High)
- DMX512, Stand Alone, RF Remote Control
- Rated Power: 500 W
- Display Screen: LCD
- * Must Clean After Every Use

TECHNICAL SPECIFICATIONS

BODY

- Rugged Metal Housing
- Internal Spark Components

ELECTRONICS

- Spark Output Fader: 0-100% (Max 13 ft)

ELECTRICAL

- Mains Power Supply: AC Mains
- Max Power Consumption: 800W
- Input Voltage: AC 11-240V, 50/60Hz

UPC

- 093674449947

OPTICS

- Zoom: 6° to 60°

DYNAMIC EFFECTS

- Spark Fountain

CONTROL

- Protocols: DMX512
- DMX Channels: 2 Channel Mode
- Remote: Wireless RF Remote
- Firmware Upgrade: Yes, USB-DMX Interface, not included.

PHYSICAL

- IP Rating: 20
- Cooling: Fan
- Data Connection: 3-PinDMX
- Power Connection: Power-CON
- Dimensions: 11.8" x 11.8" x 12.6"
- Weight: 17.6 lbs.

Box Content

- 1 x Firestorm F3
- 1 x RF Receiver
- 1 x RF Remote
- 1 x User Manual