



OSIRIS^{LED}

Indoor Curve Mobile LED Video Wall



SPECIFICATIONS:

SKU #	BB1026	BB1029
Pixel Pitch	2.6 mm	2.9 mm
LED	Black SMD 1515	Black SMD 1515
Panel Dimensions	500 x 500 x 83 mm 17.6 lbs.	500 x 500 x 83 mm 17.6 lbs.
Pixel Resolution	192 x 192	168 x 168
Module Quantity	2 x 2	2 x 2
Curvature	+/- 5°	+/- 5°
Brightness	800 Nit	800 Nit
Refresh Rate	≥3,840 Hz	≥3,840 Hz
Grayscale	16 bit	16 bit
Scan Mode	1/32	1/28
Pixel Density	147456 Dots/m2	112896 Dots/m2
Max Power Usage	150W	150W
Input Power	450W	450W
Lifespan	100,000 Hours	100,000 Hours
IP Rating	IP30 (front) IP20 (rear)	IP30 (front) IP20 (rear)
Warranty	3 Year	3 Year
Serviceability	Front and Rear	Front and Rear
Control System	Novastar	Novastar
Certifications	CE, RoHS, FCC	CE, RoHS, FCC
Special Features	Corner Protection Swappable All-In-One Power Box	Corner Protection Swappable All-In-One Power Box
Case Pack	9 Panels Per Flight Case	9 Panels Per Flight Case