


OSIRIS^{LED}

Indoor Fixed LED Video Wall



SPECIFICATIONS:

SKU #	BB1001	BB1002	BB1003
Pixel Pitch	1.9 mm	2.6 mm	3.9 mm
LED	Black SMD 1515	Black SMD 1515	Black SMD 2020
Panel Dimensions	500 x 500 x 63 mm 15.2 lbs.	500 x 500 x 63 mm 15.2 lbs.	500 x 500 x 63 mm 15.2 lbs.
Pixel Resolution	256 x 256	192 x 192	128 x 128
Module Quantity	2 x 2	2 x 2	2 x 2
Brightness	800 Nit	900 Nit	900 Nit
Refresh Rate	≥3,840 Hz	≥3,840 Hz	≥3,840 Hz
Grayscale	16 bit	16 bit	16 bit
Scan Mode	1/64	1/32	1/16
Pixel Density	262144 Dots/m ²	147456 Dots/m ²	65536 Dots/m ²
Max Power Usage	200W	200W	200W
Input Power	600W	600W	600W
Lifespan	100,000 Hours	100,000 Hours	100,000 Hours
IP Rating	IP30	IP30	IP30
Warranty	3 Year	3 Year	3 Year
Serviceability	Front	Front	Front
Control System	Novastar	Novastar	Novastar
Certifications	CE, RoHS, FCC	CE, RoHS, FCC	CE, RoHS, FCC
Special Features	Ultra-lightweight and slim design for effortless installation.	Ultra-lightweight and slim design for effortless installation.	Ultra-lightweight and slim design for effortless installation.