



OSIRIS LED

Outdoor Curve Mobile LED Video Wall



SPECIFICATIONS:

SKU #	BB1032	BB1031
Pixel Pitch	3.9 mm	3.9 mm
LED	SMD 1921	SMD 1921
Panel Dimensions	500 x 1000 x 83 mm 30.8 lbs.	500 x 500 x 83 mm 17.6 lbs.
Pixel Resolution	128 x 256	128 x 128
Module Quantity	2 x 4	2 x 2
Curvature	+/- 5°	+/- 5°
Brightness	4500 Nit	4500 Nit
Refresh Rate	≥3,840 Hz	≥3,840 Hz
Grayscale	16 bit	16 bit
Scan Mode	1/16	1/16
Pixel Density	65536 Dots/m2	65536 Dots/m2
Max Power Usage	200W	200W
Input Power	600W	600W
Lifespan	100,000 Hours	100,000 Hours
IP Rating	IP65 (front) IP54 (rear)	IP65 (front) IP54 (rear)
Warranty	3 Year	3 Year
Serviceability	Front and Rear	Front and Rear
Control System	Novastar	Novastar
Certifications	CE, RoHS, FCC	CE, RoHS, FCC
Special Features	Corner Protection Swappable All-In-One Power Box	Corner Protection Swappable All-In-One Power Box
Case Pack	6 Panels Per Flight Case	9 Panels Per Flight Case